



### DIN 6888 (Metric) And BS 46 (Imperial) Woodruff Keys



DIN 6888 (Metric) And BS 46 (Imperial) Woodruff Keys							
Woodruff Keys DIN 6888 (Metric)				Woodruff Keys BS 46 Part 1 (Imperial)			
Width W	Height H	Length L	Diameter (d2x2)	Key No.	Width W	Height h	Diameter (d2x2)
1.5	2.6	6.75	7	203	1/16	0.166 - 0.171	3/8
2	2.6	6.75	7	204	1/16	0.198 - 0.203	1/2
2	3.7	9.66	10	303	3/32	0.166 - 0.171	3/8
2	5	12.65	13	304	3/32	0.198 - 0.203	1/2
2.5	3.7	9.66	10	305	3/32	0.245 - 0.250	5/8
3	3.7	9.66	10	403	1/8	0.166 - 0.171	3/8
3	5	12.65	13	404	1/8	0.198 - 0.203	1/2
3	6.5	15.72	16	405	1/8	0.245 - 0.250	5/8
4	5	12.65	13	406	1/8	0.308 - 0.313	3/4
4	6.5	15.72	16	505	5/32	0.245 - 0.250	5/8
4	7.5	18.57	19	506	5/32	0.308 - 0.313	3/4
5	6.5	15.72	16	507	5/32	0.370 - 0.375	7/8
5	7.5	18.57	19	606	3/16	0.308 - 0.313	3/4
5	9	21.63	22	607	3/16	0.370 - 0.375	7/8
5	10	24.49	25	608	3/16	0.433 - 0.438	1
5	7.5	18.57	19	609	3/16	0.479 - 0.484	1.1/8
6	9	21.63	22	807	1/4	0.370 - 0.375	7/8
6	10	24.49	25	808	1/4	0.433 - 0.438	1
6	11	37.35	28	809	1/4	0.479 - 0.484	1.1/8
7	10	24.49	25	810	1/4	0.479 - 0.484	1.1/4
8	9	21.63	22	812	1/4	0.636 - 0.641	1.1/2
8	11	27.35	28	1008	5/16	0.433 - 0.438	1
8	13	31.43	32	1009	5/16	0.479 - 0.484	1.1/8
10	11	27.35	28	1010	5/16	0.542 - 0.547	1.1/4
10	13	31.43	32	1011	5/16	0.589 - 0.594	1.3/8
10	16	43.08	45	1012	5/16	0.636 - 0.641	1.1/2
				1210	3/8	0.542 - 0.547	1.1/4
				1211	3/8	0.589 - 0.594	1.3/8
				1212	3/8	0.636 - 0.641	1.1/2

Tolerances

DIN 688 : Width - h9 And Height - h12

Tolerances

BS 46 : Width + 0.001" And Height + 0.005"

Material
C45K Key Steel

INFORMATION AND DRAWINGS PROVIDED ARE FOR REFERENCE ONLY