

Loose Bolt Shield Anchors



Loose Bolt Shield Anchors									
Part Number	Thread Diameter	Length Under Head mm	Maximum Fixing Thickness mm	Drill Hole Diameter mm	Minimum Hole Depth mm	Embedment Depth mm	Fixture Clearance Hole mm	Minimum Structure Thickness mm	Recommended Tightening Torque Nm
ALB0610	6		55	12	50	45	8	80	6
ALB0625			70						
ALB0640			85						
ALB0810	8		60	14	55	50	10	100	14
ALB0825			75						
ALB0840			90						
ALM1010	10		70	16	65	60	12	120	27
ALB1025			85						
ALB1050			110						
ALB1075			135						
ALB1210	12		85	20	85	75	14	160	46
ALB1225			100						
ALB1240			115						
ALB1260			135						
ALB1630	16		135	25	120	110	18	200	110
ALB1630			150						
ALB1660			180						

All Steel Anchor With High Tensile Bolt For General Purpose Applications
 Finish Plated: Zinc And Yellow Passivated Minimum 5um
 Suitable For Fixing Into Concrete, Solid Brick, Dense Blockwork And Some Natural Stone

INFORMATION AND DRAWINGS PROVIDED ARE FOR REFERENCE ONLY